What is claimed is:

1. A multiple wire connector unit essentially comprising:

a male connector, a female connector, and a screwed collar for providing connection means for a plurality of wires; wherein said male connector further includes a male connector terminal, a collar journal, a sealed sleeve, and a male terminal block; said female connector further includes a female connector terminal, a collar journal, a sealed envelop, and a female terminal block; after connecting with said plurality of wires respectively, said male and said female connectors are coupled together in a unit using said screwed collar.

2. The connector unit of claim 1, wherein said male connector terminal is interposed between a front end solenoidal member of larger diameter and a rear end solenoidal member of smaller diameter, said front end solenoidal member has an inner receiving cavity in which said male terminal block having a plurality of via holes is accommodated, said rear end solenoidal member is for accepting said collar journal having a plurality of via holes to plug into, and an inner threaded sealed sleeve further sleeves over and engages with said collar journal with screw threads thereby completing assembly.

3. The connector unit of claim 1, wherein said female connector terminal is configurated into a through sleeve body with a clamping terminal formed at its front end, said clamping terminal is provided with an inner receiving cavity for accommodating said female terminal block having a plurality of via holes, said female connector terminal has a rear end solenoidal member

for receiving a collar journal having a plurality of via holes to fit in, and then an internally threaded sealed sleeve is sleeved over said collar journal and mutually screw combined.

4. The connector unit of claim 3, wherein a disc type barrier with a larger diameter is interposed between said front and clamping terminal and said rear end solenoidal member.

5. The connector unit of claim 1, wherein said screw collar is provided at one end of said female connector and has a plurality of via holes for said multiplex wires to pass through, said screwed collar encompasses said female connector terminal and combines with said front end solenoidal member of said male connector terminal with its inner threads thereby said male and said female connectors are firmly screw engaged.

6. The connector unit of claim 1, wherein said receiving cavity of said front end solenoidal member at said male connector terminal has an inner detention groove and a detention surface, while said male terminal block also has a corresponding plug and a detention surface so as to trammel with each other without rotation.

7. The connector unit of claim 1, wherein said receiving cavity in the clamping end of said female connector terminal has an inner detention groove and a detention surface, while said female terminal block also has a corresponding plug and a detention surface so as to trammel with each other without rotation.

8. The connector unit of claim 7, wherein said clamping terminal of said female connector terminal has a detention surface formed on its outer surface so as to couple firmly each other with the detention surface formed

in the receiving cavity of said male terminal block.

9. The connector unit of claim 1, wherein at least one stud tenon is provided at the side portion of said clamping terminal of said female connector to be mated with corresponding slot mortise formed in said terminal block so as to provide a tenon and mortise joint as a discrimination means for refusing incompatible mating of male and female connectors.

10. The connector unit of claim 7, wherein at least one stud tenon is provided at the side portion of said clamping terminal of said female connector to be mated with corresponding slot mortise formed in said terminal block so as to provide a tenon and mortise joint as a discrimination means for refusing incompatible mating of male and female connectors.

11. The connector unit of claim 9, wherein the number, size, and position of said stud tenon and said slot mortise can be varied according to the actual requirement so as to obtain the variety of discrimination means.